

# Material Safety Data Sheet

9025 Technology Dr. • Fishers, IN 46038-2886  
800-387-0672 • 317-570-7020 • Fax 317-570-7034  
email:info@bangslabs.com • www.bangslabs.com



## Section 1: Chemical Product and Company Identification

Date Prepared: 03/11/2002  
Part Name: **Carboxylated Polystyrene**  
Supplier: Bangs Laboratories, Inc. / a Division of Polysciences, Inc.  
9025 Technology Drive  
Fishers, Indiana 46038

## Section 2: Composition / Information on Ingredients

Carboxylated polystyrene suspended in water.

## Section 3: Hazards Identification

Eyes: mild irritation  
Skin Contact: short exposure - no irritation; repeated prolonged exposure (especially if confined) - mild irritation, possibly a mild superficial burn.  
Skin Adsorption: not likely to be absorbed in toxic amounts; possibly weak sensitizer  
Ingestion: low single dose toxicity  
Inhalation: no guide established; considered to be low hazard from inhalation  
Systemic & Other Effects: none known

## Section 4: First Aid Measures

Eyes: Flushing the eye immediately with water for 15 minutes is a good safety practice. Physician should stain for evidence of corneal injury.  
Skin: Contact may cause slight irritation. Wash off in flowing water or shower. Wash clothing before reuse. Treat as any contact dermatitis. If burn is present, treat as any thermal burn.  
Ingestion: Low in toxicity. Induce vomiting if large amounts are ingested.  
Inhalation: Remove to fresh air if effects occur. Consult medical personnel.  
Systemic & Other Effects: Human effects not established. No specific antidote. Treatment based on sound judgment of physician and the individual reactions of the patient.

## Section 5: Fire Fighting Measures

Extinguishing Media: water fog  
Special Firefighting Methods: not applicable  
Unusual Fire & Exploding Hazards: The dried resin is flammable similar to wood. Burning dry resin emits dense, black smoke. Suspended material is not flammable.


## Section 6: Accidental Release Measures

Any information listed below is to be considered in addition to internal guidelines for isolation of spill, containment of spill, removal of ignition sources from immediate area, and collection for disposal of spill by trained, properly protected clean up personnel.

*Flush area with water immediately. Avoid unnecessary exposure and contact.*

## Section 7: Handling and Storage

Ventilation: Good room ventilation usually adequate for most operations.  
Respiratory Protection: None normally needed. In cases where there is a likelihood of inhalation exposure to dried particles, wear NIOSH approved dust respirator.  
Storage: Keep from freezing. Store at 2-8°C. Material may develop bacteria odor on long-term storage. No safety problems known.



### **Section 8: Exposure Controls / Personal Protection**

Respiratory Protection: None normally needed. In cases where there is a likelihood of inhalation exposure to dried particles, wear a NIOSH approved dust respirator.

Wash / Hygienic Practices: Wash with soap and water when leaving work area and before eating, smoking, and using restroom facilities.

### **Section 9: Physical and Chemical Properties**

Boiling Point: 100°C / 212°F  
Glass Transition Temperature: 95°C  
Density: 0.95 - 1.05 g/cc  
Solubility: dispersible in water  
Appearance & Odor: white, yellowish, or brownish; milky liquid suspension; odorless

### **Section 10: Stability and Reactivity**

Stability: Stable under normal conditions. See Section 7.  
Incompatibility: May irreversibly aggregate if frozen at 0°C / 32°F. Addition of chemicals may cause coagulation.  
Hazardous Combustion or Decomposition Products: Dried resin is combustible. If burned, produces a dense, black smoke and noxious gasses (carbon dioxide and hydrocarbons).

### **Section 11: Toxicological Information**

no data

### **Section 12: Ecological Information**

no data

### **Section 13: Disposal Considerations**

In large amounts, will color streams and rivers to a milky white. Has practically no biological oxygen demand, but will settle out and form sludge or film. Large amounts may plug up sanitary sewers. Divert to pond or burn solid waste in an adequate incinerator. Flush sewers with large amounts of water.

### **Section 14: Transportation Data**

no data

### **Section 15: Regulatory Information**

no data

### **Section 16: Other Information**

BANGS LABORATORIES, INC. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose.

BANGS LABORATORIES, INC. makes no representations or warranties, either expressed or implied of merchantability, fitness for particular purposes with respect to the information set forth herein or to which the information refers. Accordingly, BANGS LABORATORIES, INC. will not be responsible for damages resulting from the use of or reliance upon this information.

**END OF MSDS**

